



Dados técnicos

	Unidades	VU 30CS/1-5	VU 35CS/1-5	VUW 26CS/1-5	VUW 32CS/1-5	VUW 36CS/1-5	VUW 40CS/1-5	VUI 32CS/1-5
Dados aquecimento								
Etiqueta energética aquecimento (A a G)								
Eficiência energética AQS (A++ a G)								
Perfil de consumo								
Eficiência energética sazonal em aquecimento		94%	94%	94%	94%	94%	94%	94%
Faixa de potência útil (P) com	50/30°C	3,9...33,3	4,3...37,7	2,7...21,0	3,9...27,0	3,9...33,3	4,3...37,7	3,9...27,0
Faixa de potência útil (P) com	80/60 °C	3,5...29,9	4,0...34,8	2,4...19,7	3,4...25,0	3,5...29,9	4,0...34,8	3,5...25,0
Potência máxima aquecimento	kW	30.6	35.7	20.4	25.5	30.6	35.7	25.5
Potência mínima aquecimento	kW	3.7	4.2	2.7	3.7	3.7	4.2	3.7
Potência de aquecimento máx. AQS	kW	34.8	39.7	26	31.8	35.6	39.7	32.6
Faixa regulação temp. aquecimento	°C	15 ... 80						
Dados produção de AQS								
Fluxo específico D (ΔT = 30 K) (EN 13203-1)	l/hora	-	-	8.7	15.1	17.1	19.4	18.5
Caudal mínimo de arranque	l/min	-	-	2	2	2	2	-
Faixa regulação temp. água quente	°C	-	-	35 ... 65	35 ... 65	35 ... 65	35 ... 65	35 ... 65
Capacidade do acumulador	litros	-	-	-	-	-	-	20
Dados elétricos								
Tensão/Frequência	V / Hz	230 / 50	230 / 50	230 / 50	230 / 50	230 / 50	230 / 50	230 / 50
Máximo consumo elétrico em aquecimento	W	80	94.6	59	84	80	94.6	84
Máximo consumo elétrico em AQS	W	110	124.8	75	95	110	124.8	115
Consumo elétrico em stand-by	W	< 2	< 2	< 2	< 2	< 2	< 2	< 2
Grau de proteção elétrica		IP X4 D	IP X4 D	IP X4 D	IP X4 D	IP X4 D	IP X4 D	IP X4 D
Dimensões								
Altura	mm	720	720	720	720	720	720	720
Largura	mm	440	440	440	440	440	440	440
Profundidade	mm	348	382	348	348	348	382	546
Peso em funcionamento	kg	36	38	36	37	37	41	57
Ligação Avanço e Retorno (aquecimento)		3/4" - 3/4"	3/4" - 3/4"	3/4" - 3/4"	3/4" - 3/4"	3/4" - 3/4"	3/4" - 3/4"	3/4" - 3/4"
Ligação Avanço e Retorno (AQS)		1/2" - 1/2"	1/2" - 1/2"	3/4" - 3/4"	3/4" - 3/4"	3/4" - 3/4"	3/4" - 3/4"	1/2" - 1/2"
Ligação de gás	mm	15						
Ligação do sistema de saída de gases	mm	60/100						
Certificação								
Categoria		II2H3P						
Classe NOx		6						
Tipo de instalação		B23, B33, B53, B53P, C13, C33, C43, C53,C83, C93						
Homologação CE		0063CU3910						